

CLAIMS

1. A user authentication system, comprising:
 - an address data storing device for storing an address data of a portable terminal owned by a user in advance by relating it to an identification data peculiar to the user for 5 identifying the user;
 - an input device for receiving an input of the identification data from the user;
 - a corresponding data generating device for generating and storing a corresponding data which corresponds to the inputted 10 identification data;
 - a corresponding data transmitting device for transmitting the corresponding data generated in the corresponding data generating device to the address data which is related to the identification data by extracting the address 15 data from the address data storing device; and also
 - a collation device for collating to check, when the corresponding data is inputted by the user through the input device, whether or not the corresponding data is consistent with the corresponding data which has been generated and stored by 20 the corresponding data generating device.

2. A user authentication system, comprising:

an input device for receiving from a user an input of an address data of a portable terminal owned by the user;

5 a corresponding data generating device for generating and
 storing a corresponding data which corresponds to the inputted
 address data;

10 a corresponding data transmitting device for
 transmitting the corresponding data generated in the
 corresponding data generating device to the address data
 received in the input device; and also

15 a collation device for collating to check, when the
 corresponding data is inputted by the user through the input
 device, whether or not the corresponding data is consistent with
 the corresponding data which has been generated and stored by
 the corresponding data generating device.

3. A user authentication system, comprising:

an address data storing device for storing an address data
of a portable terminal owned by a user in advance by relating
it to an identification data peculiar to the user for
5 identifying the user;

an input device for receiving an input of the
identification data from the user;

10 a corresponding data generating device for generating and
storing a corresponding data which corresponds to the inputted
identification data;

15 a display device for displaying the generated
corresponding data so as to be viewed by the user who has inputted
the identification data to the input device;

20 an input screen transmitting device for transmitting an
input screen data which is to be displayed in the portable
terminal of the user for requesting an input of the
corresponding data to the address data by extracting the address
data being related to the identification data from the address
data storing device; and also

25 a collation device for collating to check whether or not
the corresponding data is consistent with the corresponding
data which has been generated and stored by the corresponding
data generating device by receiving the corresponding data from
the portable terminal, which is inputted to the input screen
displayed in the portable terminal.

4. A user authentication system, comprising:

5 an input device for receiving from a user an input of an
address data of a portable terminal owned by the user;

a corresponding data generating device for generating and
storing a corresponding data which corresponds to the inputted

address data;

a display device for displaying the generated corresponding data so as to be viewed by the user who has inputted the address data to the input device;

10 an input screen transmitting device for transmitting an input screen data which is to be displayed in the portable terminal of the user for requesting an input of the corresponding data to the address data which is received in the input device; and also

15 a collation device for collating to check whether or not the corresponding data is consistent with the corresponding data which has been generated and stored by the corresponding data generating device by receiving the corresponding data from the portable terminal, which is inputted to the input screen 20 displayed in the portable terminal.

5. A data providing system, using the user authentication system according to claim 1 for performing user authentication and for providing a data used in a portable terminal to the portable terminal of the user after being authenticated, the 5 data providing system comprising:

a data request receiving device for receiving a data request inputted through the input device from a user who is authenticated as a result of the collation performed by the

collation device; and
10 a requested data transmitting device for transmitting a prescribed data which corresponds to the received request to an address data of the user.

6. The data providing system according to claim 5, wherein:

the data request receiving device comprises a portal specifying information receiving function for receiving portal 5 specifying information from a user, which specifies contents of a portal site to be accessed by the portable terminal of the user; and

the requested data transmitting device comprises a function of transmitting a site address data to the portable 10 terminal, which is accessible to a portal site being specified based on the portal specifying information.

7. The data providing system according to claim 5, wherein:

the data request receiving device comprises a deposit amount information receiving function for receiving deposit 5 amount information from the user for specifying a deposit amount for a communication fee to be used in the portable terminal of the user; and

the requested data transmitting device comprises a function of transmitting a communication fee data in an amount 10 according to the deposit amount information to the portable terminal.

8. A user authentication input apparatus, comprising: an identification data input receiving device for receiving from a user an input of an identification data which is peculiar to the user;

5 a corresponding data transmission requesting device for transmitting the inputted identification data to an authentication server connected through a network and also for requesting to the authentication server to generate a corresponding data which corresponds to the identification data 10 and transmitting it to an address data of the portable terminal owned by the user who has inputted the identification data;

15 a corresponding data input receiving device for receiving from the user an input of the corresponding data transmitted to the portable terminal of the user from the authentication server; and

a collation requesting device for requesting to the authentication server to collate to check whether or not the inputted corresponding data is consistent with the data which has been generated in the authentication server.

9. A user authentication input apparatus, comprising:
an address data input receiving device for receiving from
a user an input of an address data of a portable terminal owned
by the user;

5 a corresponding data transmission requesting device for
transmitting the inputted address data to an authentication
server connected through a network and also for requesting to
the authentication server to generate a corresponding data
which corresponds to the address data and transmitting it to

10 the address data;

 a corresponding data input receiving device for receiving
from the user an input of the corresponding data transmitted
to the portable terminal of the user from the authentication
server; and

15 a collation requesting device for requesting to the
authentication server to collate to check whether or not the
inputted corresponding data is consistent with the data which
has been generated in the authentication server.

10. A user authentication input apparatus, comprising:
an identification data input receiving device for
receiving from a user an input of an identification data which
is peculiar to the user;

5 a corresponding data generation requesting device for
transmitting the inputted identification data to an
authentication server connected through a network and for
requesting to the authentication server to generate and return
a corresponding data which corresponds to the identification
10 data, while requesting to transmit an input screen data which
is to be displayed in the portable terminal of the user for
requesting to the user an input of the corresponding data to
an address data of the portable terminal owned by the user who
has inputted the identification data; and

15 a display device for displaying the corresponding data
returned from the authentication server so as to be viewed by
the user who has inputted the identification data to the
identification data input receiving device, wherein

the corresponding data displayed in the display device
20 is a data which is inputted to the input screen displayed in
the portable terminal of the user and transmitted to the
authentication server for being collated to check whether or
not it is consistent with the data which has been generated by
the authentication server.

11. A user authentication input apparatus, comprising:
an address data input receiving device for receiving from
a user an input of an address data of a portable terminal owned

by the user;

5 a corresponding data generation requesting device for transmitting the inputted address data to an authentication server connected through a network and for requesting to the authentication server to generate and return a corresponding data which corresponds to the address data, while requesting 10 to transmit an input screen data which is to be displayed in the portable terminal of the user for requesting to the user an input of the corresponding data to the address data; and a display device for displaying the corresponding data returned from the authentication server so as to be viewed by 15 the user who has inputted the address data to the address data input receiving device, wherein

the corresponding data displayed in the display device is a data which is inputted to the input screen displayed in the portable terminal of the user and transmitted to the 20 authentication server for being collated to check whether or not it is consistent with the data which has been generated by the authentication server.

12. A user authentication server, comprising:

an address data storing device for storing an address data of a portable terminal owned by a user in advance by relating it to an identification data peculiar to the user for

5 identifying the user;

a corresponding data generating device for receiving the identification data inputted by the user from an input device connected through a network and also for generating and storing a corresponding data which corresponds to the received

10 identification data;

a corresponding data transmitting device for transmitting the corresponding data generated in the corresponding data generating device to the address data which is related to the received identification data by extracting

15 the address data from the address data storing device; and also

a collation device for collating to check whether or not the corresponding data is consistent with the corresponding data which has been generated and stored by the corresponding data generating device by receiving the corresponding data

20 inputted by the user from the input device.

13. A user authentication server, comprising:

a corresponding data generating device for receiving an address data of a portable terminal owned by a user, which is inputted by the user from an input device connected through a

5 network and also for generating and storing a corresponding data

which corresponds to the received address data;

a corresponding data transmitting device for

transmitting the corresponding data to the received address data; and also

10 a collation device for collating to check whether or not the corresponding data is consistent with the corresponding data which has been generated and stored by the corresponding data generating device by receiving the corresponding data inputted by the user from the input device.

14. A user authentication server, comprising:

an address data storing device for storing an address data of a portable terminal owned by a user in advance by relating it to an identification data peculiar to the user for 5 identifying the user;

a corresponding data generating device for receiving the identification data inputted by the user from an input device connected through a network and also for generating and storing a corresponding data which corresponds to the received 10 identification data;

a display requesting device for requesting to the input device to display the generated corresponding data so as to be viewed by the user who has input the identification data to the input device;

15 an input screen transmitting device for transmitting an input screen data which is to be displayed in the portable

terminal of the user for requesting an input of the corresponding data to the address data by extracting the address data which is related to the received identification data from 20 the address data storing device; and also

25 a collation device for collating to check whether or not the received corresponding data is consistent with the corresponding data which has been generated and stored by the corresponding data generating device by receiving the corresponding data from the portable terminal, which is inputted to the input screen displayed in the portable terminal.

15. A user authentication server, comprising:

5 a corresponding data generating device for receiving an address data of a portable terminal owned by a user, which is inputted by the user from an input device connected through a network and also for generating and storing a corresponding data which corresponds to the received address data;

10 a display requesting device for requesting to the input device to display the generated corresponding data so as to be viewed by the user who has input the address data to the input device;

an input screen transmitting device for transmitting an input screen data which is to be displayed in the portable terminal of the user for requesting an input of the

corresponding data to the received address data; and also
15 a collation device for collating to check whether or not the received corresponding data is consistent with the corresponding data which has been generated and stored by the corresponding data generating device by receiving the corresponding data from the portable terminal, which is
20 inputted to the input screen displayed in the portable terminal.

16. A portable terminal having a prescribed address data for enabling to receive data, comprising:

a function of, by a user authentication system placed at a prescribed area, receiving an input of identification data
5 peculiar to a user from an owner of the portable terminal, generating a corresponding data corresponded to the identification data, and receiving the corresponding data when the corresponding data is transmitted to the address data of the portable terminal; and
10 a function of displaying the received corresponding data in a display, wherein

the corresponding data is a data which is inputted to the user authentication system by the user to be collated to check whether or not it is consistent with the data which has been
15 generated by the user authentication system.

17. A portable terminal having a prescribed address data for enabling to receive data, comprising:

a function of, by a user authentication system placed at a prescribed area, receiving an input of an address data of a 5 portable terminal from a user who is an owner of the portable terminal, generating a corresponding data corresponded to the address data, and receiving the corresponding data when the corresponding data is transmitted to the address data of the portable terminal; and

10 a function of displaying the received corresponding data in a display, wherein

the corresponding data is a data which is inputted to the user authentication system by the user to be collated to check whether or not it is consistent with the data which has been 15 generated by the user authentication system.

18. A user authentication method, comprising:

an input receiving step for receiving from a user an input of an identification data peculiar to the user through an input device;

5 a corresponding data generating step for generating and storing a corresponding data which corresponds to the inputted identification data;

a corresponding data transmitting step for transmitting

the corresponding data generated in the corresponding data generating step to an address data of the portable terminal owned by the user of the identification data by extracting the address data from an address data storing device in which the identification data and the address data are stored in advance by being related to each other; and also

15 a collation step for collating to check, when the corresponding data is inputted by the user through the input device, whether or not the corresponding data is consistent with the corresponding data which has been generated and stored in the corresponding data generating step.

19. A user authentication method, comprising:

an input receiving step for receiving from a user an input of an address data of a portable terminal owned by the user through an input device;

5 a corresponding data generating step for generating and storing a corresponding data which corresponds to the inputted address data;

a corresponding data transmitting step for transmitting the corresponding data generated in the corresponding data generating step to the received address data; and also

10 a collation step for collating to check, when the corresponding data is inputted by the user through the input

device, whether or not the corresponding data is consistent with the corresponding data which has been generated and stored in
15 the corresponding data generating step.

20. A user authentication program for achieving, in a computer for authenticating a user when the user logs in:
an address data storing device for storing an address data of a portable terminal owned by a user in advance by relating
5 it to an identification data peculiar to the user for identifying the user;
an input device for receiving an input of the identification data from the user;
a corresponding data generating device for generating and
10 storing a corresponding data which corresponds to the inputted identification data;
a corresponding data transmitting device for transmitting the corresponding data generated in the corresponding data generating device to the address data which
15 is related to the identification data by extracting the address data from the address data storing device; and
a collation device for collating to check, when the corresponding data is inputted by the user through the input device, whether or not the corresponding data is consistent with
20 the corresponding data which has been generated and stored by

the corresponding data generating device.

21. A user authentication program for achieving, in a computer for authenticating a user when the user logs in:

an input device for receiving from a user an input of an address data of a portable terminal owned by the user;

5 a corresponding data generating device for generating and storing a corresponding data which corresponds to the inputted address data;

a corresponding data transmitting device for transmitting the corresponding data generated in the 10 corresponding data generating device to the address data received in the input device; and also

a collation device for collating to check, when the corresponding data is inputted by the user through the input device, whether or not the corresponding data is consistent with 15 the corresponding data which has been generated and stored by the corresponding data generating device.